



MATERIAL AND CONSTRUCTION

EXTRUDED ALUMINIUM SECTIONS 6063-T5

- 2mm (.080")

PERIMETER FRAME DETAILS

- CHANNEL FRAME TYPE U, DRAINABLE BLADE AND JAMBS

MULLION DETAILS

- CONTINUOUS TYPE (SECTION E), (SECTION B)
C/W BLADE BRACES ON BLADE SPANS OF 1600mm(63")
FOR CONTINUOUS EXTERNAL APPEARANCE IN
MULTIPLE SECTIONS NOT INCLUDING CORNERS

BIRDSCREENS

- ALUMINUM 13 X 13mm (1/2" X 1/2") MESH, 1.6mm(.063")
WIRE C/W EXTRUDED ALUMINUM FRAME, REMOVABLE
- GALV. 19 GAUGE 2/MESH WIRE MECHANICALLY FASTENED
- INSECT SCREEN 18 X 14 MESH ALUM. WIRE C/W FRAME

FINISH

- MILL FINISH
- ANODIZED ALUMINUM CLEAR # 17
 COLOUR (SPECIFY) _____
- PAINT ACRYLIC 5000 SERIES
 FLUOROPOLYMER 10,000 SERIES
SPECIFY COLOUR # AND MANUFACTURE

ROOF

- 2mm (.080) ALUMINUM ROOF(OTHER THICKNESSES
ARE AVAILBLE)
- 25mm (1") INSULATION C/W NEOPRENE BACKER
- ROOF TRUSS FOR 20LBS LOAD IF OTHER
PLEASE SPECIFY

ITEM #	QUANTITY	WIDTH	LENGHT	HEIGHT	REMARKS	PROJECT	
						ARCH. / ENGR.	
#1						CONTRACTOR	
#2						DATE	
#3						NOTES	
#4							
#5							
#6							